

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 1 of 13

Print date: 06/04/2016

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: SUPERCOLLE

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Not recommended for domestic use

##### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **DAVID MORAN S.A.**  
Address: Pol. Ind. C/Cueva de Viera,4  
City: Antequera  
Province: Malaga  
Telephone: +34952703550  
Fax: +34952703551  
E-mail: Fds@davidmoran.net  
Web: www.davidmoran.net

**1.4 Emergency telephone number:** +34952703550 (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 2 : Highly flammable liquid and vapour.

Repr. 2 : Suspected of damaging the unborn child.

Skin Irrit. 2 : Causes skin irritation.

STOT RE 2 : May cause damage to organs through prolonged or repeated exposure.

STOT SE 3 : May cause drowsiness or dizziness.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

H statements:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

P statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take precautionary measures against static discharge.
P271	Use only outdoors or in a well-ventilated area.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 2 of 13

Print date: 06/04/2016

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P405	Store locked up.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Contains:  
hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6))  
toluene  
acetone,propan-2-one,propanone

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 601-021-00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01-2119471310-51-0010	[1] toluene	20 - 49.99 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - Skin Irrit. 2, H315 - STOT RE 2 *, H373 ** - STOT SE 3, H336	-
Index No: 601-007-00-7 CAS No: 64742-49-0 EC No: 931-254-9 Registration No: 01-2119484651-34-0000	[1] hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6))	25 - 49.99 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Skin Irrit. 2, H315 - STOT SE 3, H336	-
Index No: 606-001-00-8 CAS No: 67-64-1 EC No: 200-662-2 Registration No: 01-2119471330-49-0016	[1] acetone,propan-2-one,propanone	10 - 19.99 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* \*\* \*\*\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

**IRRITANT PREPARATION.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 3 of 13

Print date: 06/04/2016

### **Inhalation.**

If wearing contact lenses, remove them. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

### **Eye contact.**

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

### **Skin contact.**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

### **Ingestion.**

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

## **SECTION 5: FIREFIGHTING MEASURES.**

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Recommended extinguishing methods.**

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

### **5.2 Special hazards arising from the mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

#### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### **6.2 Environmental precautions.**

Product Dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### **6.3 Methods and material for containment and cleaning up.**

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 4 of 13

Print date: 06/04/2016

contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III)::

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

### 7.3 Specific end use(s).

See technical data sheet

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
toluene	108-88-3	European Union [1]	<b>Eight hours</b>	50 (skin)	192 (skin)
			<b>Short term</b>	100 (skin)	384 (skin)
		United Kingdom [2]	<b>Eight hours</b>	50	191
			<b>Short term</b>	100	384
hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6))	64742-49-0	United Kingdom [2]	<b>Eight hours</b>	500	1790
			<b>Short term</b>	1000	3580
acetone,propan-2-one,propanone	67-64-1	European Union [1]	<b>Eight hours</b>	500	1210
			<b>Short term</b>		
		United Kingdom [2]	<b>Eight hours</b>	500	1210
			<b>Short term</b>	1500	3620

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 5 of 13

Print date: 06/04/2016

Name	DNEL/DMEL	Type	Value
toluene N. CAS: 108-88-3 N. CE: 203-625-9	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	8,13 (mg/kg bw/day)
acetone,propan-2-one,propanone N. CAS: 67-64-1 N. CE: 200-662-2	DNEL (Workers)	Inhalation, Long-term, Systemic effects	1210 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	200 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	2420 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	186 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	62 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	62 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
toluene N. CAS: 108-88-3 N. CE: 203-625-9	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
	aqua (intermittent releases)	0,68 (mg/L)
	PNEC STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
	sediment (marine water)	16,39 (mg/kg sediment dw)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
acetone,propan-2-one,propanone N. CAS: 67-64-1 N. CE: 200-662-2	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
	PNEC STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg sediment dw)
	sediment (marine water)	3,04 (mg/kg sediment dw)
	PNEC soil	29,5 (mg/kg soil dw)

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 6 of 13

Print date: 06/04/2016

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>	<b>Not recommended for domestic use</b>		
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
<b>Skin protection:</b>			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 7 of 13

Print date: 06/04/2016

### 9.1 Information on basic physical and chemical properties.

Appearance: N.A./N.A.

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: No procede

Melting point: N.A./N.A.

Boiling Point: 58 °C

Flash point: -14 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: 1

Upper Explosive Limit: 13

Vapour pressure: 99,563

Vapour density: 3.1

Relative density: Entre 0.8 y 0.95 g/cm<sup>3</sup>

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: No miscible

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: 480°C

Decomposition temperature: N.A./N.A.

Viscosity: 1600-2200

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

### 9.2. Other information.

VOC content (p/p): 75,698 %

VOC content: **581,869** g/l

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

At high temperatures can occur pyrolysis and dehydrogenation.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.

### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 8 of 13

Print date: 06/04/2016

### SECTION 11: TOXICOLOGICAL INFORMATION.

**IRRITANT PREPARATION.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

#### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
acetone,propan-2-one,propanone  67-64-1 EC No: 200-662-2	Oral	LD50	Rat	5800 mg/kg bw [1] [1] Journal of Toxicology and Environmental Health. Vol. 15, Pg. 609, 1985
	Dermal			
	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Product classified:

Reproductive toxicant, Category 2: Suspected of damaging fertility or the unborn child.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Product classified:

Specific target organ toxicity following a repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 9 of 13

Print date: 06/04/2016

Name	Ecotoxicity			
	Type	Test	Kind	Value
toluene  CAS No: 108-88-3      EC No: 203-625-9	Fish	LC50	Fish	31,7 mg/l (96 h) [1] [1] Geiger, D.L., L.T. Brooke, and D.J. Call 1990. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Volume 5. Ctr.for Lake Superior Environ.Stud., Univ.of Wisconsin-Superior, Superior, WI :332 p
	Aquatic invertebrates	LC50	Crustacean	92 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
	Aquatic plants	EC50	Algae	12,5 mg/l (72 h) [1] [1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L.Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169
acetone,propan-2-one,propanone  CAS No: 67-64-1      EC No: 200-662-2	Fish	LC50	Fish	8300 mg/l (96 h) [1] [1] Cairns, J.Jr., and A. Scheier 1968. A Comparison of the Toxicity of Some Common Industrial Waste Components Tested Individually and Combined. Prog.Fish-Cult. 30(1):3-8
	Aquatic invertebrates	LC50	Crustacean	8450 mg/l (48 h) [1] [1] Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch.Environ.Contam.Toxicol. 20(2):211-217. Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)
	Aquatic plants	EC50	Algae	7200 mg/l (96 h) [1] [1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)

### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
toluene  N. CAS: 108-88-3      EC No: 203-625-9	2,73	-	-	Low

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 10 of 13

Print date: 06/04/2016

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1133

### 14.2 UN proper shipping name.

Description: UN 1133, ADHESIVES, 3, PG II, (D/E)

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: II

### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

### 14.6 Special precautions for user.

Labels: 3



Hazard number: 33

ADR LQ: 5 L

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 11 of 13

Print date: 06/04/2016

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D  
Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
48. Toluene CAS No 108-88-3 EC No 203-625-9	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2

Asp. Tox. 1 : Aspiration toxicity, Category 1

Eye Irrit. 2 : Eye irritation, Category 2

Flam. Liq. 2 : Flammable liquid, Category 2

Repr. 2 : Reproductive toxicant, Category 2

Skin Irrit. 2 : Skin irritant, Category 2

STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2

STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Sections changed compared with the previous version:

1,8,9,11,14,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 12 of 13

Print date: 06/04/2016

### Labelling in accordance with Directive 1999/45/EC:

#### Symbols:



#### R Phrases:

R11 Highly flammable.  
R38 Irritating to skin.  
R63 Possible risk of harm to the unborn child.  
R67 Vapours may cause drowsiness and dizziness.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### S Phrases:

S9 Keep container in a well-ventilated place.  
S16 Keep away from sources of ignition - No smoking.  
S33 Take precautionary measures against static discharges.  
S51 Use only in well-ventilated areas.  
S57 Use appropriate container to avoid environmental contamination.  
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.  
S36/37 Wear suitable protective clothing and gloves.


#### Contains:

hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6))  
toluene

#### Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
108-88-3	toluene	Registered
64742-49-0	hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6))	Registered
67-64-1	acetone,propan-2-one,propanone	Registered

#### Risk classification system NFPA 704:



Health hazard: 2 (Hazardous)

Flammability: 4 (Below 73°F)

Reactivity: 0 (Stable)

#### Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
IMDG: International Maritime Code for Dangerous Goods.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## SUPERCOLLE

Version: 10

Revision date: 04/04/2016



DAVID MORÁN S.A.

Page 13 of 13

Print date: 06/04/2016

LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

### NZ Agents:

Footcom NZ Ltd  
84 Victoria Street  
Petone  
Wellington  
New Zealand

Tel: 04 569 3680  
sales@footcom.co.nz

### Emergency Telephone

Poison Centre: 0800 764 766



0800 366 826  
 P 04 569 3680 F 04 569 6973  
 E sales@footcom.co.nz  
 84 Victoria Street, Petone  
 Wellington 5012

### ADDENDUM TO SAFETY DATA SHEET

This SDS is prepared in the internationally recognised GHS format. This addendum provides information specifically for this product for New Zealand and should not be detached but rather read in conjunction with the SDS which follows and remains integral to the attached SDS.

Identification			
Product Name	Supercolle Neoprene Adhesive		
SDS Reference		Date of Issue	02/04/2020
Page 00 of 13			
Supplement to Section 1: Identification to the material and the supplier			
Company	Footcom NZ Ltd		
New Zealand Address	84 Victoria Street, Petone, Lower Hutt, Wellington 5012		
Telephone	04 569 3680		
Emergency – NZ	04 569 3680 (24 hour) or 0800 POISON (764 766)		
Supplement to Section 2: Hazard Identification			
Hazardous nature	H225 Highly Flammable Liquid and Vapour		
GHS Classification	H315 Causes Skin Irritation H319 Causes Serious Eye Irritation H411 Toxic to Aquatic Life		
HSNO Status	Hazardous according to HSNO in New Zealand		
HSNO Classification	3.1B		
Supplement to Section 15: Regulatory Information			
Group Standard	ERMA Group – HSR002662		
Other	-		
Authorised Signature and Date			
2.04.2020			