

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

570.000 Renia - Primer for PUR

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Hardener (Crosslinker)

Reserved for industrial and professional use.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	Renia Gesellschaft mbH. Chemische Fabrik	
	D	
Street:	Ostmerheimer Straße 516	
Place:	D-51109 Köln (Cologne)	
Post-office box:	910659	
	D-51076 Köln (Cologne)	
Telephone:	+49-221-630799-0	Telefax: +49-221-630799-50
e-mail:	info@renia.com	
Contact person:	Heinz Buchholz Dipl.Chem	Telephone: 16
e-mail:	labor@renia.com	
Internet:	www.renia.com	
Responsible Department:	Labor 07:30 - 16:00 Uhr	

1.4. Emergency telephone number:

+49-221-630799-0

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008 [CLP]

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225

Highly flammable liquid and vapour.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 2 of 12

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235 Keep cool.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Contains isocyanates. See information supplied by the manufacturer.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Hardener (Crosslinker)
Isocyanate containing product.

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-78-6	ethyl acetate			90 - < 95 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
26471-62-5	4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate			<0,1 %
	247-722-4	615-006-00-4		
	Carc. 2, Acute Tox. 2, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Resp. Sens. 1, Skin Sens. 1, Aquatic Chronic 3; H351 H330 H319 H335 H315 H334 H317 H412			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. Remove contaminated, saturated clothing immediately. After contact with skin, wash



Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 3 of 12

immediately with plenty of water and soap. @000000000006

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder. alcohol resistant foam. ABC powder. Atomized water. Dry sand.

Unsuitable extinguishing media

Water. High power water jet. High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Carbon monoxide Hydrocyanic acid (hydrocyanic acid). vapours of isocyanate

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Special exposure hazards arising from the substance itself, combustion products, resulting gases: In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 4 of 12

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours / aerosols must be extracted by suction immediately at point of origin.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean.
Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

Hardener (Crosslinker)

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 5 of 12

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	1468 mg/m ³
Worker DNEL, acute		inhalation	local	1468 mg/m ³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	734 mg/m ³
Consumer DNEL, acute		inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term		inhalation	local	734 mg/m ³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m ³
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	367 mg/m ³

PNEC values

CAS No	Substance	Value
141-78-6	ethyl acetate	
Freshwater		0,26 mg/l
Marine water		0,026 mg/l
Freshwater sediment		0,34 mg/kg
Marine sediment		0,034 mg/kg
Soil		0,22 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Before starting work, apply solvent-resistant skincare preparations.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Test suitability of gloves before use.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 6 of 12

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	light yellow
Odour:	ester

Test method

pH-Value: not applicable

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	77 °C DIN 53 171
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	-4 °C DIN 51 755
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits:	2,1 vol. %
Upper explosion limits:	11,5 vol. %
Ignition temperature:	460 °C DIN 51 794

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: 97 hPa DIN EN 12

(at 20 °C)

Vapour pressure: not determined

Density (at 20 °C): 0,9 g/cm³ DIN 51 757

Bulk density: not applicable

Water solubility: Decomposes in contact with water.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 7 of 12

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:
(at 20 °C)

DIN 51550

Viscosity / kinematic:

not determined

Flow time:

< 30 (3 mm)

Vapour density:

not determined

Evaporation rate:

not determined

Solvent separation test:

< 0,1 %

Solvent content:

87,5 %

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard. Explosive. The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.2. Chemical stability

Danger of polymerisation. The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions. Gas/vapour, highly flammable.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Risk of explosion by shock, friction, fire or other sources of ignition. Remove all sources of ignition. Keep away from heat. Ignition hazard. Decomposition takes place from temperatures above: > 150 °C

10.5. Incompatible materials

Keep away from: Protect against: Contact with air/oxygen. Acid, concentrated. , Oxidizing agents, strong. Reacts violently in contact with acids, amines, driers, polymerization accelerators and easily oxidized materials.

Radical former, Peroxides, Reducing agent.

10.6. Hazardous decomposition products

Hydrogen cyanide (hydrocyanic acid). Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis .

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 8 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 mg/kg	5600	Rat	
	dermal	LD50 mg/kg	18000	Rabbit	
	inhalative (4 h) vapour	LC50	58 mg/l	Rat	
26471-62-5	4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate				
	inhalative vapour	ATE	0,5 mg/l		
	inhalative aerosol	ATE	0,05 mg/l		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

May cause skin and eye irritation in susceptible persons. Contact with eyes may cause irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

There are no data available on the preparation/mixture itself.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Inhalation causes narcotic effects/intoxication.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

LD50/oral/rat = > 2000 mg/kg

Mild eye irritation (rabbit)

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

When under water, the product is transformed to poly-urea at the interface while producing CO₂. Liquid soap or water soluble solvents enhance this reaction strongly.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	3300	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 9 of 12

The product has not been tested. Product is biodegradable with difficulty.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,6

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30		

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

Further information

Avoid release to the environment. The statement is derived from the properties of the components.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethyl acetate)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	LQ4, 3 Liter
Excepted quantity:	E2
Transport category:	2
Hazard No:	33

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 10 of 12

Tunnel restriction code: D/E

Other applicable information (land transport)

: 274 - 330 - 601 - 640D

: 2

Inland waterways transport (ADN)**14.1. UN number:** UN 1993**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ethyl acetate)**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Classification code: F1

Special Provisions: 640D

Limited quantity: 1 Liter

Excepted quantity: E2

Marine transport (IMDG)**14.1. UN number:** UN 1993**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ethyl acetate)**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Marine pollutant: No

Special Provisions: -

Limited quantity: 1 Liter

Excepted quantity: E2

EmS: F-E, S-E

Other applicable information (marine transport)

Staukategorie B

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 1993**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (ethyl acetate)**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 11 of 12

IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 99,92 % (899,28 g/l)

2004/42/EC (VOC): 99,92 % (899,28 g/l)

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1.

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Revision date: 05.07.2017

Product code: 570.000

Page 12 of 12

H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

NZ Agents:

Footcom NZ Ltd
84 Victoria Street
Petone
Wellington
New Zealand

Tel: 04 569 3680
sales@footcom.co.nz

Emergency Telephone

Poison Centre: 0800 764 766

ADDENDUM TO SAFETY DATA SHEET

This SDS is prepared in the internationally recognised GHS format. This addendum provides information specifically for this product for New Zealand and should not be detached but rather read in conjunction with the SDS which follows and remains integral to the attached SDS.

Identification			
Product Name	Renia Primer for PUR		
SDS Reference	570.000	Date of Issue	02/04/2020
Page 00 of 12			
Supplement to Section 1: Identification to the material and the supplier			
Company	Footcom NZ Ltd		
New Zealand Address	84 Victoria Street, Petone, Lower Hutt, Wellington 5012		
Telephone	04 569 3680		
Emergency – NZ	04 569 3680 (24 hour) or 0800 POISON (764 766)		
Supplement to Section 2: Hazard Identification			
Hazardous nature	H225 Highly Flammable Liquid and Vapour		
GHS Classification	H319 Causes Serious Eye Irritation		
HSNO Status	Hazardous according to HSNO in New Zealand		
HSNO Classification	3.1B		
Supplement to Section 15: Regulatory Information			
Group Standard	ERMA Group – HSR002662		
Other	-		
Authorised Signature and Date			
2.04.2020			