

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

530.000 Renia - Thinner

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Solvent/Thinner.

1.3. Details of the supplier of the safety data sheet

Company name:	Renia Gesellschaft mbH. Chemische Fabrik	
	D	
Street:	Ostmerheimer Straße 516	
Place:	D-51109 Köln (Cologne)	
Post-office box:	910659	
	D-51076 Köln (Cologne)	
Telephone:	+49-221-630799-0	Telefax: +49-221-630799-50
e-mail:	info@renia.com	
Contact person:	Heinz Buchholz Dipl.Chem	Telephone: 16
e-mail:	labor@renia.com	
Internet:	www.renia.com	
Responsible Department:	Labor 07:30 - 16:00 Uhr	

1.4. Emergency telephone number:

+49-221-630799-0

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 [CLP]

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl acetate

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

cyclohexane

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006


530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 2 of 13

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P264	Wash Protective clothing thoroughly after handling.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	-------------------------------------------------------

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of organic solvents

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
141-78-6	ethyl acetate	40 - < 45 %
	205-500-4	607-022-00-5
		01-2119475103-46
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	40 - < 45 %
	265-151-9	649-328-00-1
		01-2119475133-43
	Flam. Liq. 2, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H304 H411	
110-82-7	cyclohexane	15 - < 20 %
	203-806-2	601-017-00-1
		01-2119463273-41
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H225 H315 H336 H304 H400 H410	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 3 of 13

4.1. Description of first aid measures**General information**

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator.

Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. Grease skin after contact. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed, rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Dizziness. Nausea. Headache. unconsciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate, artificial ventilation. Subsequent observation for pneumonia and lung oedema.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), alcohol resistant foam. Extinguishing powder, ABC powder. Atomized water.

Unsuitable extinguishing media

High power water jet. High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 4 of 13

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours / aerosols must be extracted by suction immediately at point of origin. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent, Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean.

Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

Solvent/Thinner.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	1468 mg/m ³
Worker DNEL, acute		inhalation	local	1468 mg/m ³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	734 mg/m ³
Consumer DNEL, acute		inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term		inhalation	local	734 mg/m ³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m ³
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	367 mg/m ³
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	5306 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1137 mg/m ³
Consumer DNEL, long-term		oral	systemic	1601 mg/kg bw/day
110-82-7	cyclohexane			
Consumer DNEL, long-term		oral	systemic	59,4 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	2016 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	206 mg/m ³
Worker DNEL, long-term		inhalation	systemic	700 mg/m ³

PNEC values

CAS No	Substance	Value
141-78-6	ethyl acetate	
Freshwater		0,26 mg/l
Marine water		0,026 mg/l
Freshwater sediment		0,34 mg/kg
Marine sediment		0,034 mg/kg
Soil		0,22 mg/kg

8.2. Exposure controls



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 6 of 13

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Before starting work, apply solvent-resistant skincare preparations.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Test suitability of gloves before use.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,5 mm

Breakthrough time (maximum wearing time) : >= 1 h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Wear anti-static footwear and clothing

Respiratory protection

Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387) Use the following filter types for cleaning waste gases: A-P2

Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless
Odour:	ester

pH-Value: Test not required.

Changes in the physical state

Melting point:	-35 °C	
Initial boiling point and boiling range:	65 - 95 °C	DIN 53 171
Sublimation point:	not determined	
Softening point:	not determined	
Pour point:	not determined	
Flash point:	-18 °C	DIN 51 755
Sustaining combustion:	No data available	

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

Vapours can form explosive mixtures with air.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 7 of 13

Lower explosion limits: 1 g/m³
Upper explosion limits: 11,5 g/m³
Ignition temperature: 200 °C DIN 51 794

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: 175 hPa DIN EN 12
(at 20 °C)

Vapour pressure: 950 hPa
(at 50 °C)

Density (at 20 °C): 0,79 g/cm³ DIN 51 757

Bulk density: not applicable

Water solubility: The study does not need to be conducted
because the substance is known to be
insoluble in water

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: 0,35 mPa·s DIN 51550
(at 20 °C)

Viscosity / kinematic: not determined

Flow time: < 30 (3 mm)

Vapour density: not determined

Evaporation rate: not determined

Solvent separation test: < 0,1 %

Solvent content: 100,00 %

9.2. Other information

Solid content: 0

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.3. Possibility of hazardous reactions

Gas/vapour, highly flammable. Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Decomposition takes place from temperatures above: > 150 °C

10.5. Incompatible materials

Acid, concentrated. , Oxidizing agents, strong.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 8 of 13

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 mg/kg	5600	Rat	
	dermal	LD50 mg/kg	18000	Rabbit	
	inhalative (4 h) vapour	LC50	58 mg/l	Rat	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	oral	LD50 mg/kg	5000	Rat	
	dermal	LD50 mg/kg	3160	Rabbit	
	inhalative (4 h) vapour	LC50	25 mg/l	Rat	
110-82-7	cyclohexane				
	oral	LD50 mg/kg	12705	Rat	
	dermal	LD50 mg/kg	2000	Rabbit	
	inhalative (4 h) vapour	LC50	20 mg/l	Rat	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

There are no data available on the preparation/mixture itself.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Inhalation causes narcotic effects/intoxication.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 9 of 13

Aspiration hazard

May be fatal if swallowed and enters airways. (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; cyclohexane)
There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Longterm fish toxicity Product is easily volatile. Product is slightly soluble in test vehicle. An aqueous dispersion has been tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 3300 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 717 mg/l	48 h	Daphnia magna		
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha					
	Acute fish toxicity	LC50 10 mg/l	96 h	Fisch		
	Acute algae toxicity	ErC50 10 mg/l	72 h	Alge		
	Acute crustacea toxicity	EC50 10 mg/l	48 h	Daphnie		
110-82-7	cyclohexane					
	Acute fish toxicity	LC50 55 mg/l	96 h	Leuciscus idus melanotus		
	Acute algae toxicity	ErC50 500 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 0,9 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

Product is biodegradable with difficulty.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,6
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	4-5
110-82-7	cyclohexane	3,4

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30		

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 10 of 13

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

Further information

The statement is derived from the properties of the components.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of waste from residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

Waste disposal number of used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose according to legislation. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. Hazardous Material: : Cyclohexane
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. Hazardous Material: : Cyclohexane
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 11 of 13



Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Marine pollutant:	No
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
----------------------------	-----



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 12 of 13

Restrictions on use (REACH, annex XVII):

Entry 28: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

Entry 57: cyclohexane

2010/75/EU (VOC): 100 % (790 g/l)

2004/42/EC (VOC): 100 % (790 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,11.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

530.000 Renia - Thinner

Revision date: 04.07.2017

Product code: 530.000

Page 13 of 13

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

NZ Agents:

Footcom NZ Ltd
84 Victoria Street
Petone
Wellington
New Zealand

Tel: 04 569 3680
sales@footcom.co.nz

Emergency Telephone

Poison Centre: 0800 764 766

ADDENDUM TO SAFETY DATA SHEET

This SDS is prepared in the internationally recognised GHS format. This addendum provides information specifically for this product for New Zealand and should not be detached but rather read in conjunction with the SDS which follows and remains integral to the attached SDS.

Identification			
Product Name	Renia Thinner		
SDS Reference	530.000	Date of Issue	02/04/2020
Page 00 of 13			
Supplement to Section 1: Identification to the material and the supplier			
Company	Footcom NZ Ltd		
New Zealand Address	84 Victoria Street, Petone, Lower Hutt, Wellington 5012		
Telephone	04 569 3680		
Emergency – NZ	04 569 3680 (24 hour) or 0800 POISON (764 766)		
Supplement to Section 2: Hazard Identification			
Hazardous nature	H225 Highly Flammable Liquid and Vapour		
GHS Classification	H304 May be fatal if swallowed and enters airways H315 Causes Skin Irritation H319 Causes Serious Eye Irritation H411 Toxic to Aquatic Life		
HSNO Status	Hazardous according to HSNO in New Zealand		
HSNO Classification	3.1B		
Supplement to Section 15: Regulatory Information			
Group Standard	ERMA Group – HSR002662		
Other	-		
Authorised Signature and Date			
2.04.2020	